





Rubino 200

Description

Rubino 200 is the completely automatic table-top vending machine of the last generation with design and technical performance at the top of the range. It is specifically designed for small and medium locations.

Available with cabinet in two versions, standard and for payment system, it dispenses up to 8 different beverages.

Accessories

- Cabinet with height-adjustable feet (w \times h \times d 410 \times 810 \times 550 mm, 23 kg)
- Cabinet with height-adjustable feet suitable for changegiver $(w \times h \times d \ 410 \times 810 \times 550 \ mm, 24 \ kg)$
- Independent water tank kit
- Timekeeper kit
- Mixer kit for tea spiral replacement with decaffeinated/barley
- Validator kit
- 5-button keypad kit
- Memory key to copy and quickly transfer machine settings
- Eva-Dts kit

Main features

- Automatically dispenses cups (up to 195), sugar and stirrers
- Saeco Brewing Unit with new pre-heating system Saeco Power Boost: top quality espresso, easy cleaning and maintenance
- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- 6 gr to 9 gr adjustable doser
- Customisable settings

User interface

- Direct access 8-button keypad for beverage selection
- 2 keys for sugar preselection
- Option to set 2 preselection keys: one for decaffeinated/barley and one for no-cup option
- 2-line, 20-character alphanumeric display



Rubino 200 Technical data Structural specifications

Structural specifications	
Dimensions ($w \times h \times d$)	410 × 765 × 535 mm
Weight	46 kg
Electrical specifications	
Power supply	230 V/50 Hz - 220 V/60 Hz - 120 V/60 Hz
Power consumption	1250 W
Water specifications	
Boiler material	brass
Water connections	
Water connection	3/4" (I – 8 bar)
Water supply	standard: water supply - optional: independent water tank kit
Independent water tank	20
Other specifications	
Cups (h 70 mm)	195
Cups type ø	70 or 73 mm
Stirrers	180
Available stirrers	90 - 105 - 115 mm
Coffee bean container	l l
Instant product container	3
Sugar container	l l
Number of selections	8
Number of preselections	up to 4
Mixer	2
Brewing unit	7 gr or 9 gr
Canisters capacity	
Coffee beans	1.5 kg
Instant coffee	0.7 kg
Milk	0.85 kg
Chocolate	1.7 kg
Tea	2.35 kg
Sugar	2.0 kg

Technical specifications

- · Pre-galvanized and painted steel-sheet body
- Thermoplastic door
- Thermoplastic cover with transparent coffee bean container
- Containers and tanks in food-contact approved polypropylene
- Water, coffee and cup-empty signal
- Software function setting the maximum number of coffee cycles permitted before the dump box is removed and emptied
- Electronically controlled boiler temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area

- Electromechanical pulse counter
- Removable cup-releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- CE, VDE and CSA approved



